



DUAL BAND BASE SECTOR ANTENNA

WiBOX SA MDB255-90-14X

WiBOX SA MDB255-90-14X is a dual band MIMO 2x2 sector antenna (2.5GHz – X; 5 GHz – X) operating at two frequency bands: 2.35 – 2.65 GHz with 12 dBi gain and 5.1 – 5.85 GHz with 14 dBi gain. The antenna can be used in point-to-multipoint (**PMP**) topology for covering medium size areas as the **hotspot in schools, halls, stadiums or another public places**. It can work indoor and outdoor (**IP 67**). It works with the systems of: **WLAN (802.11a/b/g/n/ac), WiMAX, LTE, Bluetooth, ISM, RFID**. The antenna is integrated with the top quality **WiBOX Medium** box system.

ROHS



Electrical specification

Frequency	2.35 – 2.65 GHz 5.1 – 5.85 GHz
Gain	12 dBi 14 dBi
VSWR	<2.00 <2.00
Beamwidth	30°/90° 16°/90°
Polarization	X X
Cross-Polar Isolation	>20 dB
Front-to-Back	> 20 dB
Separation between Connectors	> 20 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	2.5 kg
Connector	RJ45 & 4xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Max Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 2350 - 2650 MHz 4x 12 dBi
- Polarization X for the frequency of 2350 - 2650 MHz
- Gain for the frequency of 5100 - 5850 MHz 4x 14 dBi
- Polarization X for the frequency of 5100 - 5850 MHz
- 4 x Connector SMA
- Big, ergonomic and voluminous **WiBOX Medium** enclosure for radio equipment installation
- Outdoor Waterproof Enclosure **WiBOX Medium**
- Designed and resistant for any weather conditions
- RJ45 Waterproof System
- Grounding system protecting against lightning - DC Ground
- 36 Warranty Months


Systems

- LTE band - 7, 38, 40, 41, 46, 53, 69, 252, 255
- WLAN - 2.4 GHz, 5 GHz
- WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- Bluetooth - 2400-2483 MHz
- ISM - 2400-2483 MHz, 5725-5875 MHz


Applications

- Stadiums, Public Places
- Hotspot
- PtM Connections
- System Integration


Plots




SA MDBC255-90-14X
2.45GHz, port 1, azimuth




SA MDBC255-90-14X
2.45GHz, port 1, elev.




SA MDBC255-90-14X
2.45GHz, port 2, azimuth




SA MDBC255-90-14X
2.45GHz, port 2, elev.




SA MDBC255-90-14X
5.5GHz, port 1, azimuth



SA MDBC255-90-14X
5.5GHz, port 1, elev.



SA MDBC255-90-14X
5.5GHz, port 2, azimuth



SA MDBC255-90-14X
5.5GHz, port 2, elev.