



TRIPLE BAND PTP/CLIENT ANTENNA

WiBOX PA MMB0727-8X NF

WiBOX PA MMB0727-8X NF is antenna predicted for **4G LTE** mainly, but is compatible with **3G** and **2G** as well. The antenna improves the signal in rural/suburban and locations where the mobile signal is weak. Due to very wide working frequency range, the antenna is universal client side station for **LTE** bands like **LTE700/800/1800/1900/2100/2300/2600** (including new 800MHz frequency using for **LTE**). Due to **small dimensions, nice look and highest quality**, the system can be installed in any location, even for the most demanding customers. **WiBOX PA MMB0727-8X NF** can operate indoor and outdoor (**IP67**). The antenna is integrated with the top quality **WiBOX Medium**. It comes with **2 x NFemale** panel mount outdoor connector.


 ROHS


 IP67


 UV
RESISTANT


 ABS

Electrical specification

Frequency	<ul style="list-style-type: none"> 0.694 - 0.96 GHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
Gain	<ul style="list-style-type: none"> 7 dBi ±1 7 dBi ±1 7 dBi ±1
VSWR	<ul style="list-style-type: none"> <1.60, max < 2.00 <1.70, max < 2.00 <1.70, max < 2.00
Beamwidth	<ul style="list-style-type: none"> 70°/70° +/- 15° 70°/70° +/- 15° 70°/70° +/- 15°
Polarization	<ul style="list-style-type: none"> X X X
Cross-Polar Isolation	
Front-to-Back	<ul style="list-style-type: none"> > 10 dB > 10 dB > 10 dB
Separation between Connectors	<ul style="list-style-type: none"> > 20 dB > 20 dB > 20 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	No

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	2.5 kg
Connector	2xNF
Material	ABS
Waterproof level	IP67
Operating temperature	from -40 +70°C to °C from -40°F to 32°F
Wind resistance	120km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts


Plots

Features


- › Gain for the frequency of 694 - 960 MHz 2x 7 dBi ±1
- › Polarization X for the frequency of 694 - 960 MHz
- › Gain for the frequency of 1700 - 2200 MHz 2x 7 dBi ±1
- › Polarization X for the frequency of 1700 - 2200 MHz
- › Gain for the frequency of 2200 - 2700 MHz 2x 7 dBi ±1
- › Polarization X for the frequency of 2200 - 2700 MHz
- › 2 x Connector NF
- › Big, ergonomic and voluminous **WiBOX Medium 2xN (LTE)** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Medium 2xN (LTE)**
- › Designed and resistant for any weather conditions
- › 36 Warranty Months

Systems


- › LTE band - 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 2305-2360
- › WiMAX - 2.3 GHz, 2.5 GHz, 700 MHz
- › 3G - 2100 MHz, 850 MHz, 900 MHz
- › GSM - 1800 MHz, 1900 MHz, 850 MHz
- › RFID - 2400 - 2483 MHz, 865 - 868 MHz, 902 - 928 MHz
- › ISM - 2400-2483 MHz, 868-870 MHz
- › WLAN - 2.4 GHz
- › Bluetooth - 2400-2483 MHz




PA MMB0727-8X
800Mhz, port 1, azimuth




PA MMB0727-8X
800Mhz, port 1, elev.




PA MMB0727-8X
800Mhz, port 2, azimuth




PA MMB0727-8X
800Mhz, port 2, elev.




PA MMB0727-8X
1800Mhz, port 1, azimuth



PA MMB0727-8X
1800Mhz, port 1, elev.




PA MMB0727-8X
1800Mhz, port 2, azimuth




PA MMB0727-8X
1800Mhz, port 2, elev.




PA MMB0727-8X
2100Mhz, port 1, azimuth




PA MMB0727-8X
2100Mhz, port 1, elev.




PA MMB0727-8X
2100Mhz, port 2, azimuth




PA MMB0727-8X
2100Mhz, port 2, elev.




PA MMB0727-8X
2600Mhz, port 1, azimuth



PA MMB0727-8X
2600Mhz, port 1, elev.



PA MMB0727-8X
2600Mhz, port 2, azimuth



PA MMB0727-8X
2600Mhz, port 2, elev.