



PTP/CLIENT ANTENNA

WIBOX PA M5-24X SLIM NF

WIBOX PA M5-24X is an innovative **PTFE microstrip dual polarity X (slant) polarized (MIMO 2x2) planar antenna** operating at the frequency range of **5,1 – 5,95 GHz** with **24 dBi** gain in both polarizations. It is desired for **point-to-point (PTP)** or **point-to-multipoint (PMP)** as the client antenna, where the high-gained antennas are required. Due to **slant (+/- 45 Deg) polarization**, **PA M5-24X** can be used in interfered environment, works with **WLAN 802.11n/ac** systems. The antenna is integrated with the top quality **WIBOX Large box** system.

ROHS



Electrical specification

Frequency	5.1 - 5.95 GHz
Gain	24 dBi
VSWR	<1.80, max < 2.00
Beamwidth	8°/8°
Polarization	X
Cross-Polar Isolation	> 25 dB
Front-to-Back	> 30 dB
Separation between Connectors	> 30 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	39.2 x 39.6 x 7.7 cm 15.43 x 15.59 x 3.03 inch
Weight	2.9 kg
Connector	RJ45 & 2xN
Material	ABS
Waterproof level	IP67
Operating temperature	from -40 +70°C to °C from -40°F to 32°F
Wind resistance	km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 5100 - 5950 MHz 2x 24 dBi
- Polarization X for the frequency of 5100 - 5950 MHz
- 2 x Connector N
- Big, ergonomic and voluminous **WIBOX Large Slim** enclosure for radio equipment installation
- Outdoor Waterproof Enclosure **WIBOX Large Slim**
- Designed and resistant for any weather conditions
- RJ45 Waterproof System
- Grounding system protecting against lightning - DC Ground
- 36 Warranty Months

Systems

- WLAN - 5 GHz
- WiMAX - 5 GHz
- RFID - 5725 - 5875 MHz
- ISM - 5725-5875 MHz


Applications

- PtP connections
- PtM Connections


Compatible with

- Cambium Networks** - ePMP 1000 Connectorized Radio, ePMP 1000 GPS Sync Radio
- MIMOSA** - A5C, C5C


Plots




PA M5-24X
Port 1, azimuth



PA M5-24X
Port 1, elev.



PA M5-24X
Port 2, azimuth



PA M5-24X
Port 2, elev.