



DUAL BAND BASE SECTOR ANTENNA

WiBOX SA D4M245-8035-1115V

Antenna **WiBOX SA D4M245-8035-1115V MIMO4x4** is **dual-band 2,4&5 GHz** 4-patch directional high-performance antenna in one radome with an **installation compartment** for your device. Antenna work on 2,4&5 GHz simultaneously (**concurrent dual-band**) and it's predicted mainly for WiFi in **high or medium density** applications. SA D4M245-8035-1115V comes with No. 4 of RP-SMA/R-TNC pigtails inbuilt. It's predicted for building small cell in high-density environments like for **stadiums, lecture halls, concert halls**. The antenna is DC Grounded and contains special **WiMount** mounting kit powered by **Wireless Instruments**.

ROHS



Electrical specification

Frequency	<ul style="list-style-type: none"> 2.4 - 2.5 GHz 5 - 6 GHz
Gain	<ul style="list-style-type: none"> 11 dBi 15 dBi
VSWR	<ul style="list-style-type: none"> <1.60, max < 2.00 <1.60, max < 2.00
Beamwidth	<ul style="list-style-type: none"> 40°/80° 25°/35°
Polarization	<ul style="list-style-type: none"> V V
Cross-Polar Isolation	>40 dB
Front-to-Back	<ul style="list-style-type: none"> > 25 dB > 25 dB
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	<ul style="list-style-type: none"> 39.2 x 39.6 x 9.6 cm 15.43 x 15.59 x 3.78 inch
Weight	2.9 kg
Connector	RJ45 & 1xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	<ul style="list-style-type: none"> from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	
Regulation Range	
Weight	
Mast Dimensions Range	
Material	

Features

- > Gain for the frequency of 2400 - 2500 MHz 1x 11 dBi
- > Polarization V for the frequency of 2400 - 2500 MHz
- > Gain for the frequency of 5000 - 6000 MHz 1x 15 dBi
- > Polarization V for the frequency of 5000 - 6000 MHz
- > 1 x Connector SMA
- > Big, ergonomic and voluminous **WiBOX Large** enclosure for radio equipment installation
- > Outdoor Waterproof Enclosure **WiBOX Large**
- > Designed and resistant for any weather conditions
- > RJ45 Waterproof System
- > Grounding system protecting against lightning - DC Ground
- > 36 Warranty Months


Systems

- > LTE band - 40, 41
- > WLAN - 2.4 GHz, 5 GHz
- > WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- > RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- > Bluetooth - 2400-2483 MHz
- > ISM - 2400-2483 MHz, 5725-5875 MHz


Applications

- > System Integration


Plots




SA D4M245-8035-1115V
2.4GHz, azimuth



SA D4M245-8035-1115V
2.4Ghz, elev.



SA D4M245-8035-1115V
5.5GHz, azimuth



SA D4M245-8035-1115V
5.5GHz, elev.