



DUAL BAND BASE SECTOR ANTENNA

WiBOX SA D4M245-8035-1115V SLIM Nf

Antenna **WiBOX SA D4M245-8035-1115V SLIM NF MIMO4x4** is dual-band **2,4&5 GHz** 4-patch directional high-performance antenna in one radome with outer N Female connectors. Antenna work on 2,4&5 GHz simultaneously (**concurrent dual-band**) and it's predicted mainly for WiFi in high or medium density applications. SA D4M245-8035-1115V comes with No. 4 N Female connectors located on the bottom part of WiBOX system. It's predicted for building **small cells in high-density environments like for stadiums, lecture halls, concert halls**. The antenna is **DC Grounded** and contains special **WiMount** mounting kit powered by **Wireless Instruments**.

ROHS



UV
RESISTANT



Electrical specification

Frequency	<ul style="list-style-type: none"> 2.4 - 2.5 GHz 5 - 6 GHz
Gain	<ul style="list-style-type: none"> 11 dBi 15 dBi
VSWR	<ul style="list-style-type: none"> <1.60, max < 2.00 <1.60, max < 2.00
Beamwidth	<ul style="list-style-type: none"> 40°/80° 25°/35°
Polarization	<ul style="list-style-type: none"> V V
Cross-Polar Isolation	>40 dB
Front-to-Back	<ul style="list-style-type: none"> > 25 dB > 25 dB
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	No

Mechanic specification

Dimensions	<ul style="list-style-type: none"> 39.2 x 39.6 x 7.7 cm 15.43 x 15.59 x 3.03 inch
Weight	0 kg
Connector	RJ45 & 1xNf
Material	ABS
Waterproof level	IP67
Operating temperature	<ul style="list-style-type: none"> from -40 +70°C to °C from -40°F to 32°F
Wind resistance	km/h

Mounting Kit

Dimensions	
Regulation Range	
Weight	
Mast Dimensions Range	
Material	

Features

- › Gain for the frequency of 2400 - 2500 MHz 1x 11 dBi
- › Polarization V for the frequency of 2400 - 2500 MHz
- › Gain for the frequency of 5000 - 6000 MHz 1x 15 dBi
- › Polarization V for the frequency of 5000 - 6000 MHz
- › 1 x Connector Nf
- › Big, ergonomic and voluminous **WiBOX Large Slim** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Large Slim**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › 36 Warranty Months

Systems

- › LTE band - 40, 41
- › WLAN - 2.4 GHz, 5 GHz
- › WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- › RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- › Bluetooth - 2400-2483 MHz
- › ISM - 2400-2483 MHz, 5725-5875 MHz

Plots

