



TRIPLE BAND OMNI ANTENNA

WiSpot OA MMB0727-4V Low PIM, 2x 4.3/10 male

WiSpot OA MMB0727-4V Low PIM, 2x 4.3/10 male connector is an omnidirectional **MIMO 2x2** antenna, working in VV-polarization, it's desired for **LTE** connections. The antenna can be used for the most popular **LTE bands, frequencies 694-2700 MHz**. That antenna is predicted to be installed indoor or outdoor on the buildings as the **client antenna**, as the **hotspot** or on the moving points like **trains, buses, lorries, yachts, boats, company or standard cars** to receive Internet by **LTE**. If You are looking for the solution which will give You the Internet access everywhere, that's the antenna for You. **WiSpot OA MMB0727-4V Low PIM, 4.3/10** can be installed on the mast, a wall or the flat surface like car roofs.

ROHS



Electrical specification

Frequency	<ul style="list-style-type: none"> ☒ 0.694 - 0.96 GHz ☒ 1.7 - 2.2 GHz ☒ 2.2 - 2.7 GHz
Gain	<ul style="list-style-type: none"> ☒ 2 dBi ☒ 2 dBi ☒ 4 dBi
VSWR	<ul style="list-style-type: none"> ☒ <1.70, max < 2.00 ☒ <1.60, max < 2.00 ☒ <1.60, max < 2.00
Beamwidth	<ul style="list-style-type: none"> ☒ 360°/8° ☒ 360°/8° ☒ 360°/8°
Polarization	<ul style="list-style-type: none"> ☒ V ☒ V ☒ V
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	No

Mechanic specification

Dimensions	16 x 16 x 24 cm 6.3 x 6.3 x 9.45 inch
Weight	1.2 kg
Connector	2x4.3/10 male
Material	ABS
Waterproof level	IP67
Operating temperature	from from -40°C to 80°C to °C from 32°F to 32°F
Wind resistance	km/h

Mounting Kit

Dimensions	
Regulation Range	
Weight	
Mast Dimensions Range	
Material	

Features

- › Gain for the frequency of 694 - 960 MHz 2x 2 dBi
- › Polarization V for the frequency of 694 - 960 MHz
- › Gain for the frequency of 1700 - 2200 MHz 2x 2 dBi
- › Polarization V for the frequency of 1700 - 2200 MHz
- › Gain for the frequency of 2200 - 2700 MHz 2x 4 dBi
- › Polarization V for the frequency of 2200 - 2700 MHz
- › 2 x Connector 4.3/10 male
- › Big, ergonomic and voluminous **WiSpot + 2 cables enclosure** for radio equipment installation
- › Outdoor Waterproof Enclosure **WiSpot + 2 cables**
- › Designed and resistant for any weather conditions
- › 36 Warranty Months

Systems

- › LTE band - 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 2305-2360
- › WIMAX - 2.3 GHz, 2.5 GHz, 700 MHz
- › 3G - 2100 MHz, 850 MHz, 900 MHz
- › GSM - 1800 MHz, 1900 MHz, 850 MHz
- › RFID - 2400 - 2483 MHz, 865 - 868 MHz, 902 - 928 MHz
- › ISM - 2400-2483 MHz, 868-870 MHz
- › WLAN - 2.4 GHz
- › Bluetooth - 2400-2483 MHz