



TRIPLE BAND PTP/CLIENT ANTENNA

WiBOX PA SMB0727-5V Low PIM, 4.3/10 male

WiBOX PA SMB0727-5V Low PIM, 4.3/10 male connector is a SISO 1x1 directional antenna desired for **LTE** connections, works as **V**-polarity system. The antenna can be used for the most popular available **LTE** bands. **WiBOX PA SMB0727-5V Low PIM** can be used to build client side station operating in all available operator's bands (**the range 694-2700 MHz**). That antenna is predicted to be installed indoor and outdoor to get **LTE** signal, its aesthetic shape makes it adaptative for most of buildings. **WiBOX PA SMB0727-5V Low PIM** comes with pigtailed inside the antenna, it can be attached to the mast or the wall by **WiMount** mounting system.


 ROHS


 IP67


 UV
RESISTANT


 ABS

Electrical specification

Frequency	<ul style="list-style-type: none"> 0.694 - 0.96 GHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
Gain	<ul style="list-style-type: none"> 4 dBi 5 dBi 6 dBi
VSWR	<ul style="list-style-type: none"> <1.50, max < 2.00 <1.30, max < 1.60 <1.30, max < 1.60
Beamwidth	<ul style="list-style-type: none"> 90°/90° +/- 30° 90°/90° +/- 30° 90°/90° +/- 30°
Polarization	<ul style="list-style-type: none"> V V V
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	No

Mechanic specification

Dimensions	27.2 x 9.6 x 27.6 cm 10.71 x 3.78 x 10.87 inch
Weight	1.2 kg
Connector	1x4.3/10 male
Material	ABS
Waterproof level	IP67
Operating temperature	from from -40°C to 80°C to °C from 32°F to 32°F
Wind resistance	km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- › Gain for the frequency of 694 - 960 MHz 1x 4 dBi
- › Polarization V for the frequency of 694 - 960 MHz
- › Gain for the frequency of 1700 - 2200 MHz 1x 5 dBi
- › Polarization V for the frequency of 1700 - 2200 MHz
- › Gain for the frequency of 2200 - 2700 MHz 1x 6 dBi
- › Polarization V for the frequency of 2200 - 2700 MHz
- › 1 x Connector 4.3/10 male
- › Big, ergonomic and voluminous **WiBOX Medium + 1 cable** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Medium + 1 cable**
- › Designed and resistant for any weather conditions
- › 36 Warranty Months

Systems

- › LTE band - 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 70, 85
- › WiMAX - 2.3 GHz, 2.5 GHz, 700 MHz
- › 3G - 2100 MHz, 850 MHz, 900 MHz
- › GSM - 1800 MHz, 1900 MHz, 850 MHz
- › RFID - 2400 - 2483 MHz, 865 - 868 MHz, 902 - 928 MHz
- › ISM - 2400-2483 MHz, 868-870 MHz
- › WLAN - 2.4 GHz
- › Bluetooth - 2400-2483 MHz