



PTP/CLIENT ANTENNA

WiBOX PA D4M6-20HVX

WiBOX PA D4M6-20HVX is H&V&X (slant) polarity MIMO 3x3/4x4 panel antenna, where each radiation stream is on separated polarity. It operates at 5.6 – 6.5 GHz with 20 dBi gain in all polarizations. The antenna is predicted for point-to-multipoint (PMP) and point-to-point (PTP) connections. Due to medium gain, it can be used for medium distance links. It can work indoor and outdoor (IP67) as well. Wide frequency band (5.6 – 6.5 GHz) allows to easily find suitable frequency for the operation. It works with the WLAN 802.11n/ac systems. PA D4M6-20HVX can work with Cisco, Aruba Networks, Huawei, Xirrus, MikroTik, Ubiquiti and others. The antenna is integrated with the top quality WiBOX Extra Large box system. The antenna comes with No. 4 RP SMA connectors.

ROHS



Electrical specification

Frequency	5.6 - 6.5 GHz
Gain	20 dBi
VSWR	<2.00
Beamwidth	16°/16°
Polarization	X,H&V
Cross-Polar Isolation	
Front-to-Back	> 30 dB
Separation between Connectors	> 32 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
Weight	2.9 kg
Connector	RJ45 & 4xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Most Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- › Gain for the frequency of 5600 - 6500 MHz 4x 20 dBi
- › Polarization X,H&V for the frequency of 5600 - 6500 MHz
- › 4 x Connector SMA
- › Big, ergonomic and voluminous **WiBOX Extra Large** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Extra Large**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lightning - DC Ground
- › 36 Warranty Months

Systems

- › LTE band - 46, 47, 255
- › WLAN - 5 GHz
- › WiMAX - 5 GHz
- › RFID - 5725 - 5875 MHz
- › ISM - 5725-5875 MHz

Applications

- › PtP connections
- › PtM Connections
- › System Integration

Compatible with

- › Cisco - Aironet 3702e, Aironet 3702p, Aironet 3602e, Aironet 2702e, Aironet 2602e, Aironet 1602e, Aironet 1532e