



HIGH-DENSITY DUAL BAND BASE SECTOR ANTENNA

WiBOX SA M4DBC245-30-12HV

WiBOX SA M4DBC245-30-12HV is concurrent dual band (DBC) (2.4 and 5 GHz) H&V polarity MIMO 4x4 panel antenna. It can operate at **two frequencies simultaneously**, at 2.4 GHz and at 5 GHz. According to medium gain, it can be used on short and medium distances, for example for **hotspots in schools, stadiums, offices or some public places**. Can work also with **mobile devices**. It can work **indoor and outdoor (IP67)** as well. Wide frequency band (2.4-2.5 GHz & 5.1-5.9 GHz) allows to easily find suitable frequency for the operation. The antenna comes with No. 4 RP SMA plug connectors (it could be also with RP TNC plug, MMCX, u.FL or Nf outside connectors), and it's designed for work in **concurrent dual band technology**, which means that **SA M4DBC245-30-12HV radiates simultaneously at both operating frequencies using only one single connector for 2.4 and 5 GHz signals**. It's predicted mainly for special access points working in the systems where **two bands (frequencies) are diplexed for one antenna connector**, from the companies as **Cisco, Aruba Networks, Huawei, Xirrus** and other. The antenna is integrated with the top quality **WiBOX Medium** box system.

ROHS



Electrical specification

Frequency	<ul style="list-style-type: none"> 2.4 - 2.5 GHz 5.1 - 5.9 GHz
Gain	<ul style="list-style-type: none"> 12 dBi 12 dBi
VSWR	<ul style="list-style-type: none"> <2.00 <2.00
Beamwidth	<ul style="list-style-type: none"> 35°/35° +/- 5° 35°/35° +/- 5°
Polarization	<ul style="list-style-type: none"> H&V H&V
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	<ul style="list-style-type: none"> > 30 dB > 25 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
Weight	2.5 kg
Connector	RJ45 & 4x4x RP TNC (Cisco, Xirrus) / RP SMA (Aruba, Ruckus) / MMCX / u.FL or 4x NF outside connectors
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 2400 - 2500 MHz 4x 12 dBi
- Polarization H&V for the frequency of 2400 - 2500 MHz
- Gain for the frequency of 5100 - 5900 MHz 4x 12 dBi
- Polarization H&V for the frequency of 5100 - 5900 MHz
- 4 x Connector 4x RP TNC (Cisco, Xirrus) / RP SMA (Aruba, Ruckus) / MMCX / u.FL or 4x NF outside connectors
- Big, ergonomic and voluminous **WiBOX Extra Large** enclosure for radio equipment installation
- Outdoor Waterproof Enclosure **WiBOX Extra Large**
- Designed and resistant for any weather conditions
- RJ45 Waterproof System
- Grounding system protecting against lightning - DC Ground
- 36 Warranty Months

Systems

- LTE band - 40, 41
- WLAN - 2.4 GHz, 5 GHz
- WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- Bluetooth - 2400-2483 MHz
- ISM - 2400-2483 MHz, 5725-5875 MHz


Applications

- Stadiums, Public Places
- Hotspot
- PtP connections
- PtM Connections
- System Integration


Compatible with

- Cisco** - Aironet 3702e, Aironet 3702p, Aironet 3602e, Aironet 2702e, Aironet 2602e, Aironet 1602e, Aironet 1552E, Aironet 1552H, Aironet 1852e
- Ruckus Wireless** - ZoneFlex 7372-E
- Aruba Networks** - AP-114, AP-134, AP-104, AP-204, IAP-204, AP-92, AP-224, IAP-224, IAP-104, IAP-134, IAP-114
- Huawei** - AP 7110SN-GN, AP 5130DN, AP 6510DN-AGN, AP 6610DN-AGN
- Xirrus** - XR - 520H


Plots




SA M4DBC245-30-12HV
H-pol, azimuth, 5.5GHz




SA M4DBC245-30-12HV
H-pol, elev, 5.5GHz




SA M4DBC245-30-12HV
V-pol, elev, 5.5GHz




SA M4DBC245-30-12HV
V-pol, elev, 5.5GHz




SA M4DBC245-30-12HV
H-pol, azimuth, 2.45GHz



SA M4DBC245-30-12HV
H-pol, elev, 2.45GHz



SA M4DBC245-30-12HV
V-pol, azimuth, 2.45GHz



SA M4DBC245-30-12HV
H-pol, elev, 2.45GHz