



PTP/CLIENT ANTENNA

WIBOX PA M0407-8HV

WiBOX PA M0407-8HV is a MIMO 2x2 patch sector antenna dedicated to **TV White Space** operating at the frequency: **470-700 MHz** with **8 dBi** gain. The antenna is predicted to be used outdoor, it works in H&V polarization. It's wide beams makes it ideal solution for mobile installations as the client antenna. The aerial can be used e.g. for TV transmission. The antenna is integrated with the top quality **WiBOX Large** box system and comes with No. 2 of N Female connectors located on the bottom of the enclosure.











Electrical specification

•	
Frequency	0.47 - 0.7 GHz
Gain	7 dBi ±1
VSWR	<1.60, max < 2.00
Beamwidth	75°/75° +/- 10°
Polarization	H&V
Cross-Polar Isolation	17 dB
Front-to-Back	> 15 dB
Separation between Connectors	> 17 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	39.2 x 39.6 x 9.9 cm 15.43 x 15.59 x 3.9 inch
Weight	2.1 kg
Connector	RJ45 & 2xN
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 470 700 MHz 2x 7 dBi ±1
- > Polarization H&V for the frequency of 470 - 700 MHz
- > 2 x Connector N
- Big, ergonomic and voluminous WiBOX Large enclosure for radio equipment installation
- > Outdoor Waterproof Enclosure WiBOX Large
- Designed and resistant for any weather conditions
- > RJ45 Waterproof System
- Grounding system protecting against lighting - DC Ground
- > 36 Warranty Months

Systems

- > LTE band 71
- > WiMAX 700 MHz
- **>** GSM 400 MHz


Applications

> System Integration


Plots




PA M0407-8HV Pol. H, azimuth



PA M0407-8HV Pol. H, elev.



PA M0407-8HV Pol. V, azimuth



PA M0407-8HV Pol. V, elev.