



PTP/CLIENT ANTENNA WiBOX PA 24-15

WiBOX PA 24-15 is a **panel antenna (SISO)** operating at the frequency band of: **2.4 – 2.5 GHz** with **15 dBi** gain, in **horizontal** or **vertical** polarization (changeable on the front cover). The antenna can be used in **point-to-point (PTP)** topology for short and medium distance links as bridges, backbones, or as a client antenna. It can work **indoor and outdoor (IP 67)**. It works with the systems of: **WLAN (802.11b/g)**. The antenna is integrated with the top quality **WiBOX Medium** box system.

ROHS



Electrical specification

Frequency	2.3 - 2.5 GHz
Gain	15 dBi
VSWR	<2.00
Beamwidth	30°/30°
Polarization	V,H
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	1.6 kg
Connector	RJ45
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Max Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- Gain for the frequency of 2300 - 2500 MHz 0x 15 dBi
- Polarization V,H for the frequency of 2300 - 2500 MHz
- 0 x Connector
- Big, ergonomic and voluminous **WiBOX Medium** enclosure for radio equipment installation
- Outdoor Waterproof Enclosure **WiBOX Medium**
- Designed and resistant for any weather conditions
- RJ45 Waterproof System
- Grounding system protecting against lightning - DC Ground
- 36 Warranty Months


Systems

- LTE band - 30, 40, 41, 53
- WLAN - 2.4 GHz
- WiMAX - 2.3 GHz, 2.5 GHz
- RFID - 2400 - 2483 MHz
- Bluetooth - 2400-2483 MHz
- ISM - 2400-2483 MHz


Applications

- PtP connections
- PtM Connections
- System Integration

Plots



Radiation pattern Pol 1



Radiation pattern Pol 2