



DUAL BAND BASE SECTOR ANTENNA

WiBOX SA MDB255-90-14X

WiBOX SA MDB255-90-14X is a dual band MIMO 2x2 sector antenna (2.5GHz – X; 5 GHz – X) operating at two frequency bands: 2.35 – 2.65 GHz with 12 dBi gain and 5.1 – 5.85 GHz with 14 dBi gain. The antenna can be used in point-to-multipoint (**PMP**) topology for covering medium size areas as the **hotspot in schools, halls, stadiums or another public places**. It can work indoor and outdoor (**IP 67**). It works with the systems of: **WLAN (802.11a/b/g/n/ac), WiMAX, LTE, Bluetooth, ISM, RFID**. The antenna is integrated with the top quality **WiBOX Medium** box system.


ROHS

DC GROUND

IP67

UV RESISTANT

ABS

Electrical specification

| | |
|-------------------------------|---|
| Frequency | <ul style="list-style-type: none"> 2.35 - 2.65 GHz 5.1 - 5.85 GHz |
| Gain | <ul style="list-style-type: none"> 12 dBi 14 dBi |
| VSWR | <ul style="list-style-type: none"> <2.00 <2.00 |
| Beamwidth | <ul style="list-style-type: none"> 30°/90° 16°/90° |
| Polarization | <ul style="list-style-type: none"> X X |
| Cross-Polar Isolation | >20 dB |
| Front-to-Back | <ul style="list-style-type: none"> > 20 dB |
| Separation between Connectors | <ul style="list-style-type: none"> > 20 dB |
| Impedance | 50 Ω |
| Max Input Power | 50 W |
| Lighting Protection | No |
| DC Ground | Yes |

Mechanic specification

| | |
|-----------------------|---|
| Dimensions | 27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch |
| Weight | 2.5 kg |
| Connector | RJ45 & 4xSMA |
| Material | ABS |
| Waterproof level | IP67 |
| Operating temperature | from -40°C to 80°C from -40°F to 176°F |
| Wind resistance | 70km/h |

Mounting Kit

| | |
|-----------------------|--|
| Dimensions | 9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch |
| Regulation Range | +/- 30° |
| Weight | 0.87 kg |
| Most Dimensions Range | 25 - 65mm |
| Material | Polyamide with fiberglass + galvanized steel U-Bolts |

Features

- › Gain for the frequency of 2350 - 2650 MHz 4x 12 dBi
- › Polarization X for the frequency of 2350 - 2650 MHz
- › Gain for the frequency of 5100 - 5850 MHz 4x 14 dBi
- › Polarization X for the frequency of 5100 - 5850 MHz
- › 4 x Connector SMA
- › Big, ergonomic and voluminous **WiBOX Medium** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Medium**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lightning - DC Ground
- › 36 Warranty Months


Systems

- › LTE band - 7, 38, 40, 41, 46, 53, 69, 252, 255
- › WLAN - 2.4 GHz, 5 GHz
- › WiMAX - 2.3 GHz, 2.5 GHz, 5 GHz
- › RFID - 2400 - 2483 MHz, 5725 - 5875 MHz
- › Bluetooth - 2400-2483 MHz
- › ISM - 2400-2483 MHz, 5725-5875 MHz


Applications

- › Stadiums, Public Places
- › Hotspot
- › PtM Connections
- › System Integration


Plots




SA MDBC255-90-14X
2.45GHz, port 1, azimuth




SA MDBC255-90-14X
2.45GHz, port 1, elev.




SA MDBC255-90-14X
2.45GHz, port 2, azimuth




SA MDBC255-90-14X
2.45GHz, port 2, elev.




SA MDBC255-90-14X
5.5GHz, port 1, azimuth



SA MDBC255-90-14X
5.5GHz, port 1, elev.



SA MDBC255-90-14X
5.5GHz, port 2, azimuth



SA MDBC255-90-14X
5.5GHz, port 2, elev.