



PTP/CLIENT ANTENNA

WiBOX PA M23-19HV

WiBOX PA M23-19HV is dual polarity HV panel antenna with 19 dBi gain (frequency 2200-2500 MHz), designed to operate at **MIMO 2x2** system. The antenna is predicted for point-to-point (PTP) or point-to-multipoint (PMP) as the client antenna, in interfered environments. **WiBOX PA M23-19HV** can work indoor and outdoor (IP67). Due to wide operating frequency range this antenna can operate in the systems like **Bluetooth, WLAN 2.4GHz or American S Band (225, 235)**. The antenna is integrated with the top quality **WiBOX Large Slim** and comes with **2 x N Female** connectors.


 ROHS


 DC GROUND


 IP67


 UV RESISTANT


 ABS

Electrical specification

Frequency	2.2 - 2.5 GHz
Gain	19 dBi ±1
VSWR	<1.40, max < 1.70
Beamwidth	20°/20° +/- 2°
Polarization	H&V
Cross-Polar Isolation	
Front-to-Back	> 25 dB
Separation between Connectors	> 35 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	39.2 x 39.6 x 7.7 cm 15.43 x 15.59 x 3.03 inch
Weight	0 kg
Connector	RJ45 & 2xN
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 70°C from -40°F to 158°F
Wind resistance	km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mount Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- › Gain for the frequency of 2200 - 2500 MHz 2x 19 dBi ±1
- › Polarization H&V for the frequency of 2200 - 2500 MHz
- › 2 x Connector N
- › Big, ergonomic and voluminous **WiBOX Large Slim** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Large Slim**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lightning - DC Ground
- › 36 Warranty Months


Systems

- › LTE band - 30, 40, 41, 53
- › WLAN - 2.4 GHz
- › WiMAX - 2.3 GHz, 2.5 GHz
- › RFID - 2400 - 2483 MHz
- › Bluetooth - 2400-2483 MHz
- › ISM - 2400-2483 MHz


Applications

- › PtP connections
- › PtM Connections


Plots




PA M23-19HV
Pol. H, azimuth



PA M23-19HV
Pol. H, elev.



PA M23-19HV
Pol. V, azimuth



PA M23-19HV
Pol. V, elev.