



#### **DUAL BAND BASE SECTOR ANTENNA**

# WiBOX SA M4DBC245-35-15VV

Antenna WiBOX SA M4DBC245-35-15VV MIMO4x4 is dual-band 2,4&5 GHz 4patch directional high-performance antenna in one radome with an **installation** compartment for your device. Antenna work on 2,4&5 GHz simultaneously (concurrent dual-band) and it's predicted mainly for WiFi in high or medium density applications. SA M4DBC245-35-15VV comes with No. 4 of RP-SMA/RP-TNC pigtails inbuilt. It's predicted for building small cell in high-density environments like for **stadiums**, **lecture halls**, **concert halls**. The antenna is DC Grounded and contains special **WiMount** mounting kit powered by **Wireless** Instruments.











#### Electrical specification

ateur iout specimenties	•
Frequency	≥ 2.4 - 2.5 GHz ≤ 5 - 6 GHz
Gain	⊠11 dBi ⊠15 dBi
VSWR	≤<1.60, max < 2.00 ≤<1.60, max < 2.00
Beamwidth	⊠40°/80° ⊠25°/35°
Polarization	⊠ V ⊠ V
Cross-Polar Isolation	>40 dB
Front-to-Back	⊠> 25 dB ⊠> 25 dB
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

## Mechanic specification

Dimensions	39.2 x 39.6 x 9.9 cm 15.43 x 15.59 x 3.9 inch
Weight	2.9 kg
Connector	RJ45 & 1xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	7Ωkm/h

#### Mounting Kit

Dimensions Regulation Range Weight Mast Dimensions Range Material

#### **Features**

- Gain for the frequency of 2400 2500 MHz 1x 11 dBi
- > Polarization V for the frequency of 2400 -
- > Gain for the frequency of 5000 6000 MHz 1x 15 dBi
- > Polarization V for the frequency of 5000 - 6000 MHz
- > 1 x Connector SMA
- ▶ Big, ergonomic and voluminous **WiBOX** Large enclosure for radio equipment installation
- > Outdoor Waterproof Enclosure **WiBOX** Large
- > Designed and resistant for any weather conditions
- > RJ45 Waterproof System
- Grounding system protecting against lighting DC Ground
- > 36 Warranty Months

#### **Systems**

- LTE band 40, 41, 46, 47, 53, 252, 255
- > WI AN 2 4 GHz 5 GHz
- > WiMAX 2.3 GHz, 2.5 GHz, 5 GHz
- » RFiD 2400 2483 MHz, 5725 5875 MHz
- > Bluetooth 2400-2483 MHz
- ) ISM 2400-2483 MHz, 5725-5875 MHz

### **Applications**

> System Integration

# Plots


SHELLEN FILE STEELS



SA D4M245-8035-1115V 2.4GHz, azimuth



SA D4M245-8035-1115V 2.4Ghz, elev.



SA D4M245-8035-1115V 5.5GHz, azimuth



SA D4M245-8035-1115V 5.5GHz, elev.