



PTP/CLIENT ANTENNA

WiBOX PA 24-19

WiBOX PA 24-19 is a **panel antenna (SISO)** operating at the frequency band of: **2.4 – 2.5 GHz** with **19 dBi** gain, in **horizontal** or **vertical** polarization (changeable on the front cover). The antenna can be used in **point-to-point (PTP)** topology for medium distance links as bridges, backbones, or as a client antenna. It can work **indoor and outdoor (IP 67)**. It works with the systems of: **WLAN (802.11b/g)**. The antenna is integrated with the top quality **WiBOX Large** box system.

ROHS



Electrical specification

Frequency	2.4 - 2.5 GHz
Gain	19 dBi
VSWR	<2.00
Beamwidth	16°/16°
Polarization	V,H
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	39.2 x 39.6 x 9.9 cm 15.43 x 15.59 x 3.9 inch
Weight	2.73 kg
Connector	RJ45
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Most Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- › Gain for the frequency of 2400 - 2500 MHz 0x 19 dBi
- › Polarization V,H for the frequency of 2400 - 2500 MHz
- › 0 x Connector SMA
- › Big, ergonomic and voluminous **WiBOX Large** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Large**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lightning - DC Ground
- › 36 Warranty Months


Systems

- › LTE band - 40, 41, 53
- › WLAN - 2.4 GHz
- › WiMAX - 2.3 GHz, 2.5 GHz
- › RFID - 2400 - 2483 MHz
- › Bluetooth - 2400-2483 MHz
- › ISM - 2400-2483 MHz


Applications

- › PtP connections
- › PtM Connections
- › System Integration

Plots



Radiation pattern Pol 1



Radiation pattern Pol 2