



TRIPLE BAND PTP/CLIENT ANTENNA

WiBOX PA MMB0727-8HVX-10m-SMA

WiBOX PA MMB0727-8HVX-10m-SMA is MIMO 2x2 antenna, working in X-Pol and H/V polarization (depend of mounting position) predicted for **4G LTE** mainly, but is compatible with **3G** and **2G** as well. The antenna improves the signal in rural/suburban and locations where the mobile signal is weak. Due to very wide working frequency range, the antenna is universal client side station for **LTE** bands like **LTE700/800/1800/1900/2100/2300/2600** (including new 800MHz frequency using for **LTE**). Due to **small dimensions, aesthetic look and highest quality**, the system can be installed in any location, even for the most demanding customers. **WiBOX PA MMB0727-8HVX-10m-SMA** can operate indoor and outdoor (**IP67**). The antenna is integrated with the top quality **WiBOX Medium**. It comes with **2x 10m cable with SMA male connector** (loss on cable below 3dB).

ROHS



Electrical specification

Frequency	<ul style="list-style-type: none"> ☒ 0.694 - 0.96 GHz ☒ 1.7 - 2.2 GHz ☒ 2.2 - 2.7 GHz
Gain	<ul style="list-style-type: none"> ☒ 8 dBi ±1 ☒ 8 dBi ±1 ☒ 8 dBi ±1
VSWR	<ul style="list-style-type: none"> ☒ <1.60, max < 1.80 ☒ <1.70, max < 1.80 ☒ <1.70, max < 1.80
Beamwidth	<ul style="list-style-type: none"> ☒ 70°/70° +/- 15° ☒ 70°/70° +/- 15° ☒ 70°/70° +/- 15°
Polarization	<ul style="list-style-type: none"> ☒ H&V or X ☒ H&V or X ☒ H&V or X
Cross-Polar Isolation	
Front-to-Back	<ul style="list-style-type: none"> ☒ > 10 dB ☒ > 10 dB ☒ > 10 dB
Separation between Connectors	<ul style="list-style-type: none"> ☒ > 20 dB ☒ > 20 dB ☒ > 20 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 9.6 x 27.6 cm 10.71 x 3.78 x 10.87 inch
Weight	2.5 kg
Connector	2xSMA male on 10m cable
Material	ABS
Waterproof level	IP67
Operating temperature	from from -40°C to 80°C to °C from 32°F to 32°F
Wind resistance	km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- ▶ Gain for the frequency of 694 - 960 MHz
2x 8 dBi ±1
- ▶ Polarization H&V or X for the frequency of
694 - 960 MHz
- ▶ Gain for the frequency of 1700 - 2200
MHz 2x 8 dBi ±1
- ▶ Polarization H&V or X for the frequency of
1700 - 2200 MHz
- ▶ Gain for the frequency of 2200 - 2700
MHz 2x 8 dBi ±1
- ▶ Polarization H&V or X for the frequency of
2200 - 2700 MHz
- ▶ 2 x Connector SMA male on 10m cable
- ▶ Big, ergonomic and voluminous **WiBOX
Medium + 2 cables SMA enclosure** for
radio equipment installation
- ▶ Outdoor Waterproof Enclosure **WiBOX
Medium + 2 cables SMA**
- ▶ Designed and resistant for any weather
conditions
- ▶ Grounding system protecting against
lighting - DC Ground
- ▶ 36 Warranty Months

Systems

- ▶ LTE band - 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12,
13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28,
29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41,
44, 53, 65, 66, 67, 68, 69, 70, 85
- ▶ WiMAX - 2.3 GHz, 2.5 GHz, 700 MHz
- ▶ 3G - 2100 MHz, 850 MHz, 900 MHz
- ▶ GSM - 1800 MHz, 1900 MHz, 850 MHz
- ▶ RfID - 2400 - 2483 MHz, 865 - 868 MHz,
902 - 928 MHz
- ▶ ISM - 2400-2483 MHz, 868-870 MHz
- ▶ WLAN - 2.4 GHz
- ▶ Bluetooth - 2400-2483 MHz

Plots

