



BASE SECTOR ANTENNA **WiBOX SA M5-45-19HV**

WiBOX SA M5-45-19HV is an H&V polarity **MIMO 2x2 sector antenna** operating at a frequency range of: **5.1 - 5.9 GHz** with **19 dBi** gain. The antenna is predicted for **point-to-multipoint (PMP)** connections, it has narrow beamwidth so it can be used for covering small and medium areas as **a base station** for client stations or as the **hotspot in schools, halls, stadiums or another public places**. It can work **indoor and outdoor (IP 67)**. It works with the **WLAN 802.11n/ac** systems. The antenna is integrated with the top quality **WiBOX Extra Large** box system.

ROHS



Electrical specification

Frequency	5.1 - 5.95 GHz
Gain	19 dBi
VSWR	<2.00
Beamwidth	8°/45°
Polarization	H&V
Cross-Polar Isolation	
Front-to-Back	
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
Weight	3 kg
Connector	RJ45 & 2xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mount Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- › Gain for the frequency of 5100 - 5950 MHz 2x 19 dBi
- › Polarization H&V for the frequency of 5100 - 5950 MHz
- › 2 x Connector SMA
- › Big, ergonomic and voluminous **WiBOX Extra Large** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Extra Large**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lighting - DC Ground
- › 36 Warranty Months


Systems

- › LTE band - 46, 47, 252, 255
- › WLAN - 5 GHz
- › WiMAX - 5 GHz
- › RFID - 5725 - 5875 MHz
- › ISM - 5725-5875 MHz


Applications

- › Stadiums, Public Places
- › Hotspot
- › PtM Connections
- › System Integration


Plots




Radiation pattern Port 1 Pol 1



Radiation pattern Port 1 Pol 2



Radiation pattern Port 2 Pol 1



Radiation pattern Port 2 Pol 2