



## BASE SECTOR ANTENNA

# WiBOX SA M5-90-17X

**WiBOX SA M5-90-17X** is an **X-polarity (slant) MIMO 2x2 sector antenna** operating at a frequency range of: **5.0 - 6.0 GHz** with **17 dBi** gain. The antenna is predicted for **point-to-multipoint (PMP)** connections, can be used for covering medium and big areas as **a base station** for client stations or as the **hotspot in schools, halls, stadiums or another public places**. Due to **slant (+/- 45 Deg) polarization, SA M5-90-17X** can be used in interfered environment. It can work **indoor and outdoor (IP 67)**. It works with the **WLAN 802.11n/ac** systems. The antenna is integrated with the top quality **WiBOX Extra Large** box system.

ROHS



### Electrical specification

Frequency	5 - 6 GHz
Gain	17 dBi ±1
VSWR	<2.00
Beamwidth	8°/80°
Polarization	X
Cross-Polar Isolation	25 dB
Front-to-Back	> 24 dB
Separation between Connectors	> 22 dB
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

### Mechanic specification

Dimensions	29.2 x 48.6 x 10.6 cm 11.5 x 19.13 x 4.17 inch
Weight	2.9 kg
Connector	RJ45 & 2xSMA
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

### Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Most Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

### Features

- › Gain for the frequency of 5000 - 6000 MHz 2x 17 dBi ±1
- › Polarization X for the frequency of 5000 - 6000 MHz
- › 2 x Connector SMA
- › Big, ergonomic and voluminous **WiBOX Extra Large** enclosure for radio equipment installation
- › Outdoor Waterproof Enclosure **WiBOX Extra Large**
- › Designed and resistant for any weather conditions
- › RJ45 Waterproof System
- › Grounding system protecting against lightning - DC Ground
- › 36 Warranty Months


### Systems

- › LTE band - 46, 47, 252, 255
- › WLAN - 5 GHz
- › WiMAX - 5 GHz
- › RFID - 5725 - 5875 MHz
- › ISM - 5725-5875 MHz


### Applications

- › Stadiums, Public Places
- › Hotspot
- › PtM Connections
- › System Integration


### Plots




SA M5-90-17X  
Port 1, azimuth



SA M5-90-17X  
Port 1, elev.



SA M5-90-17X  
Port 2, azimuth



SA M5-90-17X  
Port 2, elev.