

Wireless Instruments Sp. z o.o. ul. Kosciuszki 27, 52-116 Iwiny, Poland Tel1: +48 601 366 369, +48 577 667 761 http://www.wireless-instruments.com



HIGH-DENSITY DUAL BAND BASE SECTOR ANTENNA WIBOX SA M3DBC245-120-8V NF

Wireless Instrumnets three element **MIMO 3x3 2.4/5 GHz dual-band** antenna for Wi-Fi is rugged and high-performance panel for outdoor and indoor applications. **WiBOX SA M3DBC245-120-8V NF** is 3-Element Patch Antenna predicted mainly for high-density installations where high gain and wide beamwidth is required. The system offers relatively high gain with wide horizontal beam and low F/B ratio, which makes it unique solution on the market. The antenna is designed to work with 2.4-GHz/5-GHz Access Points (like Cisco, Aruba, Huawei and others), offers IP67 for whole system and No. 3 of N Female connectors located on the connector pannel. The antenna is integrated with **WiBOX Medium** enclosure by Wireless Instruments which offers the installation compartment for electronic stuff. **WiMount** mounting system which comes with the antenna enables wall or mast mounting.



ROHS

Electrical specification

•	
Frequency	≥ 2.4 - 2.5 GHz ≤ 4.6 - 6.4 GHz
Gain	⊠ 8 dBi ⊠ 8 dBi
VSWR	⊠ <1.60, max < 1.80 ∑ <1.60, max < 1.80
Beamwidth	⊠ 120°/60° ⊠ 120°/90°
Polarization	⊠V ⊠V
Cross-Polar Isolation	>25 dB
Front-to-Back	≥ 20 dB ≥ 20 dB
Separation between Connectors	
Impedance	50 Ω
Max Input Power	50 W
Lighting Protection	No
DC Ground	Yes

Mechanic specification

Dimensions	27.2 x 27.6 x 9.6 cm 10.71 x 10.87 x 3.78 inch
Weight	1.8 kg
Connector	RJ45 & 1xN Female
Material	ABS
Waterproof level	IP67
Operating temperature	from -40°C to 80°C from -40°F to 176°F
Wind resistance	70km/h

Mounting Kit

Dimensions	9.9 x 10.5 x 14.8 cm 3.9 x 4.13 x 5.83 inch
Regulation Range	+/- 30°
Weight	0.87 kg
Mast Dimensions Range	25 - 65mm
Material	Polyamide with fiberglass + galvanized steel U-Bolts

Features

- > Gain for the frequency of 2400 2500 MHz 1x 8 dBi
- > Polarization V for the frequency of 2400 -2500 MHz
-) Gain for the frequency of 4600 6400 MHz 1x 8 dBi
- > Polarization V for the frequency of 4600 - 6400 MHz
- >1 x Connector N Female
- > Big, ergonomic and voluminous WiBOX Medium enclosure for radio equipment installation
- > Outdoor Waterproof Enclosure **WiBOX** Medium
- Designed and resistant for any weather conditions
- > RJ45 Waterproof System
- Grounding system protecting against lighting - DC Ground
- > 36 Warranty Months

Systems

- » LTE band 40, 41, 46, 47, 53, 252, 255
- > WLAN 2.4 GHz, 5 GHz
- > WiMAX 2.3 GHz, 2.5 GHz, 5 GHz
- > RFiD 2400 2483 MHz, 5725 5875 MHz
- > Bluetooth 2400-2483 MHz
-) ISM 2400-2483 MHz, 5725-5875 MHz

Applications

- > Stadiums, Public Places
- > Hotspot
- > PtM Connections
- > System Integration

Vireless Instruments